



FORSTHOFF-P2

Agile, light automatic welder for advertising banners and vehicle tarpaulins



Highlights

- **Ideal automatic welder for advertising banners and vehicle tarpaulins**
- **Speed and temperature continuously adjustable**
- **Economical and operator-friendly**
- **Also usable for overlap, hem and welt welding**

Description

The Forsthoff-P2 is the agile and light hot-air automatic welder, ideal for advertising banners and vehicle tarpaulins. Also suitable for overlap, hem and welt welding of tarpaulins made of PVC, PE or PP.

The FORSTHOFF-P2 automatic welder is the efficient and agile universal machine for welding truck tarpaulins, tents, awning fabrics and advertising banners. The hot-air welder produces overlap seams of 20, 30, 40 or 45 mm and can also be converted for welding in welt cords. In addition, the machine can easily be used with a hem-welding accessory to produce hems of 20 mm and 30 mm and of 40 mm and 45 mm. Accessories for welt welding, roof welding and band welding are also available for this machine.

The heating power of up to 4000 W 230 V AC is continuously adjustable from 20 to 700 °C and can thus be individually matched to the different materials. After the welding head is swung in, the FORSTHOFF-P2 starts automatically. In addition, the continuously variable speed setting of the advanced motor generation, with a travel performance of up to 18 metres/min, together with the hold-down device, ensures wrinkle-free welding and thus an optimal welding result. A secure pressure on the tarpaulin is provided by a three-point support.

Thanks to a new generation of nozzles, tarpaulin fabrics can be welded at a speed of up to 11 metres/min. The machine also has a sturdy carrying handle and a telescopic guide handle that can be individually adjusted to the user's height. The agile and slim housing design makes the FORSTHOFF-P2 ideal for use in the vehicle-tarpaulin and advertising-banner sector.

Technical data

Voltage	230V; 120V
Power	up to 4000W 230V; 2200W 120V (depending on seam width)
Frequency	50/60 Hz
Temperature	20 – 700 °C
Weld seam width	20, 30, 40, 45 mm
Welding speed	up to 18 m/min
Dimensions	Length 535 mm, width 280 mm, height 350 mm (without guide handle)
Weight	23.9 kg incl. weight and handle
Conformity marks	CE; EAC
Protection class	II



FORSTHOFF-P2

Technical changes and errors excepted.